

General Equipment list - Europe

GENERAL SPECIFICATIONS_____

• L.O.A	17,12m	56'2"
Hull length	15,98m	52'5"
• L.W.L.	15,40m	50'6"
• Beam	5,00m	16'5"
 Standard draft (T-keel) 	2,50m	8'2"
Standard ballast weight (Cast iron)) 4 500kg	9,918 lbs
 Performance draft (T-keel) 	3,02m	9'11"
· Ballast weight performance (Cast i	ron/	
Lead)	4 510kg	9,940 lbs
 Air draft (excluding antennae) 	25,88m	85'
· Performance air draught (excludin	g	
antennae)	26,88m	88'
 Light displacement 	15 599kg	34,380 lbs
 Fuel capacity (standard) 	400Ľ	106 US Gal
 Fresh water capacity (standard) 	720L	190 US Gal
Engine power:		
- Sail drive (standard)	80 HP	80 HP
 Propeller shaft (Option) 	110 HP	110 HP
	1	

ARCHITECTS / DESIGNERS _____

- Naval Architect: BISCONTINI YACHT DESIGN
- Outside & interior design: LORENZO ARGENTO

EC CERTIFICATION

- Category A 10 people
 Category B 12 people
 Category C 14 people

STANDARD SAILS DIMENSIONS

CLASSICAL MAST ALUMINUM

 Mainsail Furling genoa (105 %) Code 0 Asymmetric spinnaker I 	87,00m ² 78,90m ² 179,00m ² 254,00m ² 21,95m 6,40m	936 sq/ft 849 sq/ft 1,926 sq/ft 2,730 sq/ft 72' 21'
• J	6,40m	21'
• P	22,00m	72 <i>'</i> 2"
• E	6,80m	22'4"

CARBON CLASSICAL MAST (+ 1m / 3'3")

 Performance version mainsail Furling genoa (105 %) Code 0 Asymmetric spinnaker 	91,00m² 82,00m² 185,00m² 265,00m²	979 sq/ft 882 sq/ft 1,990 sq/ft 2,850 sq/ft
• I	22,90m	75'2"
• J	6,40m	21'
• P	23,00m	75'6"
• E	6,80m	22'4"



3 cabins 2 heads version:



3 cabins 3 heads - Skipper's cabin version:





General Equipment list - Europe

STANDARD EQUIPMENT

CONSTRUCTION

- Design in accordance with European Directive requirements and according to CE certification
- ISO 12215 certified structure
- Balsa sandwich infusion hull
- Vacuum infused structural inner liner (Fabrics resin) bonded to the hull
- Deck in glass fibre/balsa wood sandwich infusion, with non-slip "diamond point" surface
- Cast iron keel attached with bolts and bonded stainless steel backplate
- Twin rudders hung with stainless steel stock
- White coloured hull Aluminum grey hull decoration
- 8 Hull portholes

DECK EQUIPMENT

RIGGING

- · Depending on version:
- Black lacquered aluminum classical mast tapered, deck stepped,
- 3 Aft swept spreaders,
- Dyform Rigging,

Dyform backstay crowfoot with manual hydraulic piston to starboard (hydraulic unit optional),

Harken fixed blocks at foot of mast,

- Harken Switch mainsail track (without traveller)
- **Performance carbon classical mast** tapered, deck-stepped (+ 1m / 3'3", Weight saving: 100kg / 220 *lbs*)

3 Aft swept spreaders

ROD Rigging

Textile backstay crow's foot with manual hydraulic piston to starboard

- Harken fixed blocks at foot of mast
- Harken Switch mainsail track (without traveller)
- Lacquered aluminum Racing boom with LED lighting (warm white)
- Black Racing lacquered aluminum rigid kicking strap with Dyneema
- tackle and friction rings (hydraulic available as an option)Genoa track on the roof with traveller and hauling line controlled from the cockpit
- Manual Genoa furler below deck
- 1 mainsail attachment point at bottom of cockpit with 1 stand-up block
- · German system (Two-way mainsheet at the helm station)
- All lines brought back to the helm stations (except boom topping lift)
- Dyneema Complete running rigging:
- Mainsheet halyard sheave block,
- Genoa halyard,
- Boom uphaul (polyester) with cleat on mast,
- Mainsheet,
- 2 Genoa sheets,
- 2 Automatic reefing system
- 7 halyard clutches to port, 4 to starboard
- HARKEN Black Magic blocks
- 2 Spinnaker sheet chain plates/code 0
- Running rigging hidden
- 2 Flag halyards

WINCHES

- 1 Manual self-tailing winch to starboard (H50.2 STP)
- 1 Electric self-tailing winch to port (H50.2 STPE)
- 2 Manual Genoa winches (H70.2 STP)
- 2 Aluminum Speed Grip winch handles
- Stowage of which handles in dedicated space in rope bags

February 03, 2021 - (non-binding document)

SAILS

Boast supplied without sail

MOORING LINES - MOORING

- Polyester bowsprit with integrated anchoring gear and bobstay with spinnaker chainplate (for Code 0 and asymmetric spinnaker)
- Self-draining chain locker, Clench bolt, Piston-driven cover
- Single roller stainless steel bow fitting
- 12 V 1 500 W vertical electrical windlass Remote control in mooring locker
- 6 Black anodised aluminum mooring cleats (Length: 0,40m / 1'4")
- Stainless steel chafing plate

SAIL LOCKER

Access through T70 deck hatch, Passage width: 0,65 x 0,65m / 2'2" x 2'2"

- Stainless steel ladder
- Shelving and stowage trays
- LED lighting
- 1 230V socket

SAFETY ON DECK

- 1 Black lacquered stainless steel open pulpit
- · 2 Black lacquered stainless steel aft pulpits with integrated fairlead
- 1 Black lacquered stainless steel central aft pulpit (Height: 960mm / 3'2")
- 2 Black lacquered stainless steel handrails on the roof
- 1 Lifebuoy support bracket on aft pulpit
- Wooden flagstaff (1 m/3'3") with integrated support on deck
- Dual textile lifelines and black lacquered stainless steel stanchions (Height: 620mm / 2') Side boarding gate on either side
- Emergency ladder on pushpit

COCKPIT

- Self-draining cockpit
- Teck decking
- · 2 Sail lockers below cockpit seating
- 2 Stowage lockers behind the cockpit with stainless steel support for the fenders (650 x 390mm / 2'2'' x 1'3'')
- 1 Access hatch to tender garage
- 1 Integrated housing in catwalks for diesel deck filler and shore power socket
- 3 water deck fillers at the forward end of the roof on the catwalks
- 1 Gas locker on forward deck next to anchor chain locker, space of 2 bottles
- Dottles
 Natural solid wood slatted cockpit benches
- Natural solid wood slatted cockpit benche
 Side helmsman's seat, wooden slats
- Side neimsman's seat, wooden sla
 Foldaway helmsman foot chock
- 2 Removable footrests at the rear of the helm station
- Z Removable footrests at the rear of the helm
 2 Steering wheel consoles:
- Black composite helm (diameter 1 100 mm/3'7") fixed on white lacquered aluminum pedestal
- Steering gear at the helm station
- Stainless steel steering chain transmission system
- Black lacquered stainless steel hand rail
- 1 Emergency tiller
- 1 Steering compass on port console
- Engine throttle and control panel on starboard
- 1 Cockpit shower with mixer tap in the tender garage

liferaft: 0.96m x 0.59m x 0.40m / 3'2" x 1'11" x 1'4")

• Courtesy lighting (7 LED lighting points, warm white lighting)

1 PPMA folding companionway door in the bottom of the cockpit -Sliding hatch made of PMMA
Liferaft locker in front of the companionway (Space for 12 place

Code Bénéteau V12771 (D) Eng



SWIM PLATFORM / AFT TRANSOM

- Fully opening transom, convertible to bathing platform (2,61m x 0,93m / 8'7" x 3'1")
- 3 Folding access steps to the cockpit to starboard
- Electrically controlled opening on console
- · Natural solid wood decking on swim platform
- 1 Stainless steel, removable bathing ladder with dedicated stowage in the cockpit

TENDER GARAGE

Accessible from the platform and from the cockpit Can be used to house a Highfield UL240 type tender (2,48m x 1,69m x 0,80m / 8'2" x 5'7" x 2'7")

1 Touch-operated ceiling LEDs

INTERIOR

- Alpi teak woodwork and white lacquered wood on base units and bulkheads
- Alpikord teak flooring
- · Lounge Falcon 162 fabric interior upholstery
- Mattresses in the cabins (HR foam 35 kg/m3, thickness 120 mm/5")
- Beige padded ceilings (and Macadamia in the central part of the saloon)

Standard version: 3 cabins + 2 heads



COMPANIONWAY

- Headroom: 2,00m / 6'7"
- Saloon companionway with 5 suspended Alpikord teak non-slip steps, LED lighting below each step
- · 2 Valencia Meteor encased stainless steel handrails

SALOON

Headroom: 2,00 - 1,97m / 6'7" / 6'6"

Starboard saloon:

- Very comfortable Lounge type L-shaped sofa:
- seats with HR26 and HR30 foam
- softness thanks to the finish with hollow fibres + padding
- Coffee table, wooden top with moulded beading, access to bottle rack opposite the seat
- Storage under bench seats
- 1 Electrical panel to starboard incorporated into a piece of furniture for access to electrical connections
- 2 Portholes with integrated blind
- 2 Coachroof windows including opening porthole with mosquito net
- · 2 Opening deck hatches with mosquito screen/blinds
- Indirect LED lighting below the soft and the upper part of the portholes
- 1 Adjustable reading light
- 1 dual USB port
- 1 230V socket
- Audio:
- Fusion RA70N entertainment system
- 2 Interior loudspeakers
- 2 Waterproof exterior speakers

General Equipment list - Europe

Port saloon:

- · Wooden table with integrated sliding extension leaf
- Face-to-face bench seats with extension (can seat up to 6 diners)
- 2 Portholes with integrated blind
- Storage under bench seats
- 1 Deep storage unit against bulkhead + 1 Valet tray (unless air conditioning option chosen)
- Indirect LED lighting on the upper part of the portholes
- 1 230V socket close to forward bulkhead
- Pillar with beige cover

GALLEY - PORT

- Headroom: 2,01m / 6'7"
- C-shaped galley
- · Corian Glacier White work top with moulded teak beading
- 1 1 rectangular stainless steel sink 1 Mixer tap with hot/cold water under pressure
- 1 Gas cooker 3 burners Stainless steel/grill fitted on swivel joints (19L) - Stainless steel protection handrail - Stowage below the oven with drop-down door - Tempered glass cover on the hotplate
- 1 Stowage on work top with top opening (Space for optional 36 L stainless steel cool box)
- 1 3 drawer storage on the work top (Space for the dishwasher option)
- 12 V 174 L fridge with integrated 16 L freezer (-18 °C), 1 Front opening door
- Fitted lockers and closed shelving
- 1 Bin (20L)
- 1 Base unit: 1 drawer on the side, 2 doors, 1 shelf
- 2 Opening portholes with mosquito nets

OWNER'S CABIN

Headroom: 2,01 - 1,96m / 6'7" - 6'5"

- Central double bed (2,00m x 1,60m 1,15m / 6'9" x 5'3" 3'9") with Lounge Greige 160 fabric padded bedstead
- 1 Bed access sideboard
- 1 Chair on each side of bed with Lounge Falcon 162 fabric
- 2 Shoe stowage beneath the bed
- · 2 Hanger closets, with incorporated LED lighting
- 1 Central full-height unit with LED lighting: 4 drawers at the bottom, 1 door with 4 shelves, mirror inside the door
- 2 Night tables
- 2 Flexible and adjustable bedside lamps
- 1 T70 flush deck hatch with blind/mosquito net
- 2 Portholes with rigid sliding blind
- 1 230 V power socket on each side of the bed
- 1 dual USB port outlet on each side of the bed
- LED indirect lighting + Spot lighting
- 2 PRIVATE HEADS

<u>To starboard:</u>

- Headroom: 1,92m / 6'4"
- 1 Manual toilet
- 1 80 L / 13 US Gal rigid holding tank
- Work top in Corian Glacier White
- 1 Integrated polyester basin Mixer tap
- 1 Cabinet Mirror
- · Toilet accessories
- 1 Deck hatch with mosquito screen/blind
- LED indirect lighting + Spot lighting

<u>to port:</u>

- Headroom: 1,97m / 6'6"
- · Shower with seat and wooden shower base
- 2 Open stowage trays
- 1 Deck hatch with mosquito screen/blind
- LED indirect lighting



General Equipment list - Europe

PORT AFT CABIN

- Headroom: 1,92m / 6'4"
- 1 Double bed (2,04m x 1,40m / 6'8" x 4'7")
- 1 Hanging locker, 1 Cupboard with shelves, with incorporated LED lighting
- 2 Lockers with top opening along the hull
- 1 Bed access sideboard
- 1 Drawer under the bed
- 1 Large stowage under the bed, top opening (location for air conditioning option)
- 1 Flexible, swivelling reading light at bedhead
- 1 Flexible and adjustable reading light on the hanging locker
- 1 dual USB port
- 1 230V socket
- 1 Porthole with rigid sliding blind
- 1 Opening window with below cockpit seat with pleated blind
- 2 Opening windows on coaming with pleated blind (1 with the 3 heads version)

STARBOARD AFT CABIN

Headroom: 1,92m / 6'4"

- 1 Double bed (2,04m x 1,40m / 6'8" x 4'7")
- 1 Hanging locker, 2 lockers with top opening along the hull
- 1 Bed access sideboard
- 1 Drawer under the bed
- 1 Large stowage under the bed, top opening (location for air conditioning option)
- 1 Flexible, swivelling reading light at bedhead
- 1 Flexible and adjustable reading light on the hanging locker
- 1 USB socket
- 1 230V socket
- 1 Porthole with rigid sliding blind
- · 2 Opening windows with below cockpit seat with pleated blind
- 1 Opening window on coaming with pleated blind

AFT STARBOARD HEAD COMPARTMENT

Headroom: 1,95m / 6'5"

Access from the saloon or the starboard aft cabin

- Separate shower 1 Mixer tap White polyester shower base
- · Corian Glacier White work top with self-draining storage
- 1 Manual toilet
- 1 80 L / 21 US Gal rigid holding tank
- 1 Washbasin 1 Mixer tap
- 1 Cabinet + Storage space under the basin
- 2 Mirrors
- Toilet accessories
- 1 Opening porthole on coaming in side window, opaque film, mosquito screen

3 cabins 3 heads version (Option)



This head stands between the galley and the after port cabin: single hanging locker and one opening porthole in the aft cabin

AFT PORT HEAD COMPARTMENT

Headroom: 2,03m / 6'8"

Access by the aft starboard cabin

- Polyester work top with integrated basin 1 Mixer tap 1 Shower -White polyester shower base
- 1 Manual toilet
- 1 50 L / 13 US Gal rigid holding tank
 - 1 Bathroom cabinet 2 doors
 - 1 Mirror above the washbasin
- Toilet accessories
- 1 Opening porthole on coaming in side window, opaque film, mosquito screen
- 1 Fixed window on coaming, opaque film



General Equipment list - Europe

ENGINE

- · Engine Yanmar Diesel:
- 80 HP/80 HP, Sail Drive, Common Rail (standard)
- 110 HP/110 HP, Propeller shaft, Common Rail (Option) · Engine control at the starboard helm station - Control panel
- · Engine compartment:
- Soundproofing foam
- Ventilation: 2 air intakes and 1 forced air outlets
- Automatic LED lighting
- · Engine data visible on the B&G screen
- 1 Alternator (12V / 125 Ah)
- 2 Rotomoulded diesel tanks 2 x 200 L/2 x 53 US Gal (under aft berth port and starboard) - Electronic gauge - Low level alarm -1 Deck filler
- · Filters: Seawater Diesel Water separator
- · Foldaway three-blade propeller
- 1 Engine access through companionway (opening with 2 gas struts)
- · 2 Engine access through aft cabins

PLUMBING

- 1 Rotomoulded freshwater tank 380 L / 100 US Gal, under berth in forward cabin - 1 Deck filler
- 2 Rotomoulded freshwater tanks 2 x 150L / 2 x 40 US Gal, under saloon floor, port and starboard - 1 Deck filler
- · Pressurised electric water pump Expansion tank Inline filter
- 40 L / 11 US Gal Electric water heater (engine use)
- 1 Rigid black water holding tank for each WC
- · Electrical shower drain pumps 1 Electric bilge pump
- 1 Manual bilge pump
- Transfer valves easily accessible from the companionway

GAS

- 1 Box for 2 gas bottles in the anchor locker (Diameter: 0,28m / 11"x Height: 0,45m / 1'6")
- · Regulator and safety tap
- · Gas leak detector

MISCELLANEOUS ITEMS _____

Smoke detector

ELECTRICITY

- 12 V electrical panel (Breaker, Voltmeter, Water gauge, Fuel gauge, Battery warning, Fuel warning, Water warning) + dual USB port + Navicolor 3.5" screen
- Radio controlled wireless light switches (no battery) for lighting (excluding heads)
- Ship Control technology control numerous functions from the navigation screens (or from a tablet or smartphone using a dedicated app):
- Anchoring and masthead navigation lights
- Lighting of boom, spreaders (optional), underwater spotlights (optional)
- Courtesy light in cockpit
- Direct lighting
- Deck searchlight
- Inverter (Option)
- Fridge
- Water unit
- Bilge pumps
- Air conditioning (Option) - Generator (Option)
- Audio - Control of levels (diesel, fresh water, black water)
- Battery monitoring
- 12V circuit
- 3 AGM service batteries (140 Ah)
- 1 AGM engine battery (100 Ah)
- · Battery cut-off switch easily accessible from the companionway
- 1 Battery charger (60 Ah)
- 1 Power distributor
- 11 115V Sockets:
 - 2 in the forward cabin
 - 1 in the forward port head
 - 1 in the aft cabins
 - 1 in the saloon (Starboard) - 1 at chart table
 - 2 in galley
 - 1 in the engine compartment
 - 1 in the sail locker
- · 6 Dual USB socket:
- 2 in the forward cabin
- 1 in the aft cabins
- 1 on the electrical panel
- 1 at chart table
- 1 Shore power socket 230 V
- LED lighting:
- Overhead lights, with dimmer
- Reading lights
- Indirect lighting, with dimmer
- · LED navigation lights:
 - 1 Masthead light
 - 1 Steaming light
- 1 Anchor light on masthead Deck searchlight (Halogen)
- · Wire runs for option cables



General Equipment list - Europe

TRIM LEVEL & PACKS

TRIM LEVEL _____

	CONFORT	LUXE
Coastal B&G Pack		
• 1 Harken Performa H50.2 STPEH starboard electric manoeuvring winch (in lieu of standard)		-
Windlass control in cockpit with chain counter		
Tilting transom remote control		
 Retractable bow thruster + 4 Dedicated batteries (50 Amps - 12V) + 1 Battery charger (30 Amps - 24V) 		
 TECMA electric fresh water/sea water WC in the owner's head 		
IBS sensor		
2 Additional 140 ampères service batteries		
Additional 40 ampères battery charger		
Electrical engine control on the starboard console		
Mosquito nets for opening portholes		
Offshore B&G Pack		
 2 Teak cockpit tables with additional leaves (2 on the sides, 1 in the centre) on stainless steel pedestal and Charcoal Grey cover 		
• Outside cockpit upholstery, Sunbrella Terry beige seats and backrests (terrycloth), Filter foam 80 mm/3" thickness (Density: 60F + 20S)		
Spring mattress in the owner's cabin (thickness: 180mm / 7")		
Quiet Flush fresh water/seawater electric WC in the aft starboard head		

ELECTRONICS PACKS: B&G

	COASTAL (included in the Confort trim level)	OFFSHORE (included in the Luxe trim level)
 Port and starboard helm stations: 1 12" Zeus^{3S} wide wireless multi-function touchscreen (GPS, Chart plotter, Card reader - Navionics Silver cartography included) H5000 unit: 	-	-
 Aeriel Wind Sensor (pole 1 m/3'3'):Windvane, Anenometer Sensor (Log, Speedometer, Temperature) 	•	-
PC interface		
V100 VHF radio fixed to the chart table		
Windex Windvane	•	
 Protective covers for helm & consoles (Charcoal Grey) 		
B&G H5000 autopilot with keyboard on port console		
WR10 Wireless autopilot remote control		•

FASTNET PACK (implies pack Offshore)

• 3 Mast foot repeaters (20 x 20)

V100B VHF upgrade (with AIS)
H60 wireless VHF set



General Equipment list - Europe

RIGGING PACKS

MAINSAIL WINCH PACK (Compatible with the 2 masts)

- Self-tailing HARKEN Performa (H50.2 STPEH) electric winch on polyester turret in centre of cockpit
- Standard German System replaced by 1 Dyneema mainsheet

DOWNWIND PACK (Compatible with the 2 masts)

- · 2 Additional halyard clutches to starboard
- · 2 HARKEN Black Magic blocks for spinnaker sheet/code 0
- 1 HARKEN Black Magic block for spinnaker tackline with return on dedicated cleat in cockpit
- 1 Dyneema sheaved halyard with block for spinnaker or code 0
- 1 Dyneema halyard for spinnaker
- 1 Spinnaker tackline with return on dedicated cleat in cockpit Barber hauler (Chain plate on bulwark)

STAYSAIL RIGGING PACK (Compatible with the 2 masts -Requires hydraulic unit option)

- 1 Clutch to starboard
- · 1 Wichard double chainplate on forward deck for removable forestav
- · 1 Dyneema halyard sheave with block for staysail

SELF-TACKING RIGGING PACK (Compatible with all masts and all rigging packs)

- · Self-tacking jib hardware (sheet only)
- 1 Self-tacking jib track with traveller
- 1 Jib sheet clutch to starboard

CARBON MAST SAILS PACK

- Mainsail (91 m²/979 sg/ft) and Genoa (82 m²/882 sg/ft) North Sails NPL tour, dark grey
- Charcoal Grey lazy bag + lazy jack

ALUMINUM SAILS MAST PACK

- Mainsail (87 m²/936 sq/ft) and Genoa (82 m²/882 sq/ft) North Sails NPL tour, dark grey
- Charcoal Grey lazy bag + lazy jack

MOORING PACK

- Delta 32 kg/71 *lbs* anchor (galvanized steel)
 Chain (Diameter: 12mm / ¹/₂" Length: 40m / 131')
 Line (Diameter: 22mm / ⁷/₈" Length: 50m / 164')
- 6 Fenders:
 - 4 XL (Diameter: 300mm / 12" Length: 880mm / 2'11")
- 2 L (Diameter: 250mm / 10" Length: 700mm / 2'4")
 4 Moorings lines (Diameter: 18mm / ¹¹/₁₆" Length: 15m / 49'3")

MOORING PACK (inflatable)

- Delta 32 kg/71 /bs anchor (galvanized steel)
 Chain (Diameter: 12mm / ¹/₂" Length: 40m / 131)
 Line (Diameter: 22mm / ⁷/₈" Length: 50m / 164')
 6 Fenders (Diameter: 360mm / 1'2" Length: 1 200mm / 3'11")
 4 Moorings lines (Diameter: 18mm / ¹¹/₁₆" Length: 15m / 49'3")

OPTIONS

NAVIGATION ELECTRONICS: B&G

- 4G Radar
- Chart table: 12" Zeus^{3S} wide wireless multi-function touchscreen
- V100B VHF upgrade (with AIS)
- H60 wireless VHF set
- Forward Scan Sensor (Forward underwater vision)

RIGGING - SAILS

- FurlerBoom V-shaped boom furler, black lacquered, epoxy glassfibre casing/carbon spindle (requires carbon mast version + hydraulic unit option), Integrated LED lighting for the cockpit area
- · Hydraulic unit (for carbon mast): Hydraulic textile backstay on piston + Hydraulic kicker tackle on unit (2 Functions / 2 speeds)
- Hydraulic unit (for aluminum mast): ROD rigging and hydraulic textile backstay on piston + Hydraulic kicker tackle on unit (2 Functions / 2 speeds)
- · Electric Genoa furler below deck
- Aluminum black lacquered canoe boom with hydraulic piston, Sparcraft (Requires hydraulic unit option), Integrated LED lighting for the cockpit area
- · Code 0 with North Sails NPL tour furler, laminated, dark grey for aluminum mast
- Code 0 for carbon mast

WINCHES

2 Electric Harken Performa genoa sheet winches (H70.2 STPEH)



HULL - DECK - COCKPIT_

- · Pearl grey gel-coat (Hull & Bowsprit)
- Metallic hull paint (Hull Aft transom Gunwale Bowsprit) Solid wood slatted side decks option required
- Slatted solid wood side decks
- Natural solid wood decked roof
- Retractable capstan (Bow)
- Dolce 51 cockpit upholstery (requires Luxe trim level, as a replacement for the Terry beige upholstery)
- Electrical bases + mattress for the 2 cockpit tables (for the sun deck bed function) - in the choice: Terry Beige or Dolce 51, requires Luxe trim level
- Sprayhood with LED lighting, Strataglass windows, Charcoal Grey
- Bimini Charcoal Grey (sprayhood option required)
- Bimini for helm stations, Charcoal Grey
- Sunshade for the cockpit, Charcoal Grey
- Sunshade on foredeck, Charcoal Grey
- LED lighting of spreaders
- Retractable stern thruster
- Carbon or white composite helm
- Retractable NOMEN black anodised cleats (in lieu of standard)
- Accommodation ladder
- Outboard engine bracket
- Polyester folding gangway (2,60m / 8'6")
- Electric inflator/deflator for tender and fenders (portable, batterypowered)
- Shore fresh water supply
- Seawater/fresh water deck washing pump
- 3 Underwater lights (1 forward, 2 aft)
- 1,20 m/3'11" carbon flagstaff (in lieu of standard)
- Tender launching system (Manual winch, 1 roller)
- 32 kg/71 lbs stainless steel anchor upgrade for anchoring pack
- Stainless steel round, painted lifelines and stanchions

General Equipment list - Europe

INTERIOR EQUIPMENT

LAYOUT VERSIONS

- 3 cabins 2 heads version
- 3 cabins 3 heads version
- Skipper cabin replacing the sail locker of the foredeck: Access through T70 deck hatch, Stainless steel ladder, 1 Berth, Toilet, Washbasin, Shower, 1 dual USB port

AMBIANCE

- Interior woodwork: Alpi oak 3 gloss + Alpikord oak floorings
- Interior upholstery according to colour chart: Fabrics, Leather, Nubuck, Ultraleather

MULTIMEDIA

- TV pre-assembly on lifting system, in the saloon
- TV pre-assembly, in the forward cabin (on bulkhead)
- Hifi APOLLO + Bose 2.1 speakers, in the saloon (in lieu of standard)

DOMESTIC APPLIANCES

- Dishwasher for 6 sets
- Built-in 22 L grill and microwave combined oven
- Wine cellar 23 bottles
- 3 kg washer dryer
- 36 L cool box with access from the galley work top, stainless steel tank (temperature adjustable from +10 °C to -12 °C)
- 2 Stainless steel fridge drawers (2 x 95L) in lieu of standard

ON BOARD COMFORT EQUIPMENT

- Spring mattress in the aft cabins (thickness: 160mm / 6")
- Generator (7,5 KVA, 230V, 50Hz)
- Watermaker (60 l/h / 16 US Gal/h)
- Air conditioning 44 000 BTU
- (+ Shore socket extension cord 15m / 49'3') 32A • Forced air heating fuel
- Safe, in the forward cabin
- 12V / 230V inverter 2 000 VA
- Electric battery switch (connected to the Ship Control, controls powering on or shut-off of batteries remotely)
- Lithium battery replacing the AGM batteries Weight saving: Approximately 170 kg / 375 lbs (requires Confort trim level)
- Seawater electric pump, in galley
- Lee cloth (Aft cabins & Saloon sofa)